

C1 22424

SEQUENCE NO. (MDE USE ONLY)

STATE OF MARYLAND WELL COMPLETION REPORT

FILL IN THIS FORM COMPLETELY PLEASE TYPE

THIS REPORT MUST BE SUBMITTED WITHIN 45 DAYS AFTER WELL IS COMPLETED.

COUNTY NUMBER

A554547

(THIS NUMBER IS TO BE PUNCHED IN COLS. 3-6 ON ALL CARDS)

ST/CO USE ONLY DATE Received

DATE WELL COMPLETED

Depth of Well

PERMIT NO.

FROM "PERMIT TO DRILL WELL"

MM DD YY 10 22 14

MM DD YY 10-9-14

22 300' 26 (TO NEAREST FOOT)

OK 5/27/15 sc 28 29 30 31 32 33 34 35 36 37

OWNER

Toll Brothers

WELL SITE ADDRESS

11203 Independence Way TOWN

Ellicott City

SUBDIVISION

Hemlock Crossing

SECTION

LOT

44

WELL LOG

Not required for driven wells

STATE THE KIND OF FORMATIONS PENETRATED, THEIR COLOR, DEPTH, THICKNESS AND IF WATER BEARING

Table with columns: DESCRIPTION, FEET (FROM, TO), check if water bearing. Rows include Brown mica, Gray mica, White, Gray mica, White, Gray mica.

GROUTING RECORD

WELL HAS BEEN GROUTED (Y/N), TYPE OF GROUTING MATERIAL (CEMENT/BENTONITE CLAY), NO. OF BAGS, NO. OF POUNDS, GALLONS OF WATER, DEPTH OF GROUT SEAL.

CASING RECORD

casings types insert appropriate code below (ST/PL/CO/OT), MAIN CASING TYPE, Nominal diameter, Total depth.

OTHER CASING (if used)

Table for OTHER CASING with columns: diameter inch, depth (feet) from, to.

screen type or open hole

SCREEN RECORD

insert appropriate code below (ST/BR/PL/HO/OT), DEPTH (nearest ft.)

NUMBER OF UNSUCCESSFUL WELLS: 0

WELL HYDROFRACTURED (Y/N)

CIRCLE APPROPRIATE LETTER

- A WELL WAS ABANDONED AND SEALED WHEN THIS WELL WAS COMPLETED
E ELECTRIC LOG OBTAINED
P TEST WELL CONVERTED TO PRODUCTION WELL

I HEREBY CERTIFY THAT THIS WELL HAS BEEN CONSTRUCTED IN ACCORDANCE WITH COMAR 26.04 04 "WELL CONSTRUCTION" AND IN CONFORMANCE WITH ALL CONDITIONS STATED IN THE ABOVE CAPTIONED PERMIT...

DRILLERS LIC. NO. M 5 D 009

DRILLERS SIGNATURE (MUST MATCH SIGNATURE ON APPLICATION)

LIC. NO. D

GRAVEL PACK IF WELL DRILLED WAS FLOWING WELL INSERT F IN BOX 68

MDE USE ONLY (NOT TO BE FILLED IN BY DRILLER)

TELESCOPE CASING, LOG INDICATOR, OTHER DATA

C 3

PUMPING TEST

HOURS PUMPED (nearest hour) 3, PUMPING RATE (gal. per min.) 6, METHOD USED TO MEASURE PUMPING RATE 100, WATER LEVEL (distance from land surface) BEFORE PUMPING 35, WHEN PUMPING 70, TYPE OF PUMP USED (for test) S submersible

PUMP INSTALLED

DRILLER INSTALLED PUMP (YES/NO), IF DRILLER INSTALLS PUMP, THIS SECTION MUST BE COMPLETED FOR ALL WELLS, TYPE OF PUMP INSTALLED PLACE (A,C,J,P,R,S,T,O) IN BOX 29, CAPACITY: GALLONS PER MINUTE (to nearest gallon) 7, PUMP HORSE POWER 3/4, PUMP COLUMN LENGTH (nearest ft.) 280, CASING HEIGHT (circle appropriate box and enter casing height) above 49, LAND SURFACE below 02 (nearest foot)

LATITUDE 39.234905, LONGITUDE 76.829504 (DEFAULT COORD. WGS 84)

NOTES:

33 / 8.2 = 4 bags/10'

