

C 1 19389

SEQUENCE NO. (MDE USE ONLY)

STATE OF MARYLAND WELL COMPLETION REPORT

THIS REPORT MUST BE SUBMITTED WITHIN 45 DAYS AFTER WELL IS COMPLETED.

(THIS NUMBER IS TO BE PUNCHED IN COLS. 3-6 ON ALL CARDS)

COUNTY NUMBER

ST/CO USE ONLY DATE Received

DATE WELL COMPLETED

Depth of Well

PERMIT NO. FROM "PERMIT TO DRILL WELL"

OWNER: Tall MD VTH LTD Partnership
WELL SITE ADDRESS: 14905 Merriweather Dr
TOWN: Glenelg, MD
SUBDIVISION: SECTION 2 LOT 28

WELL LOG

Not required for driven wells

STATE THE KIND OF FORMATIONS PENETRATED, THEIR COLOR, DEPTH, THICKNESS AND IF WATER BEARING

Table with columns: DESCRIPTION, FEET (FROM, TO), check if water bearing. Rows include Sandy soil, Gray Rock, Broken Rock, Brown Rock, Gray Rock.

GRROUTING RECORD

WELL HAS BEEN GROUTED (Y/N)
TYPE OF GROUTING MATERIAL: CEMENT (CM), BENTONITE CLAY (BC)
NO. OF BAGS: 75, NO. OF POUNDS: 350
GALLONS OF WATER: 1875
DEPTH OF GROUT SEAL: 5 to 400 ft.

CASING RECORD

MAIN CASING TYPE: PL (PLASTIC)
Nominal diameter top (main) casing: 60 inch
Total depth of main casing: 70 feet

OTHER CASING (if used)

Table for OTHER CASING with columns: diameter inch, depth (feet) from, to.

SCREEN RECORD

screen type or open hole: PL (PLASTIC)
DEPTH (nearest ft.): 1

- List of well identifiers: 1) 39.260059/77.032963, 2) 39.259888/77.032980, 3) 39.259964/77.032994, 4) 39.259900/77.033013, 5) 39.259852/77.033030

WELL HYDROFRACTURED: YES (Y) NO (N)

CIRCLE APPROPRIATE LETTER: A (WELL ABANDONED AND SEALED), E (ELECTRIC LOG OBTAINED), P (TEST WELL CONVERTED TO PRODUCTION WELL)

I HEREBY CERTIFY THAT THIS WELL HAS BEEN CONSTRUCTED IN ACCORDANCE WITH COMAR 26.04.04 "WELL CONSTRUCTION" AND IN CONFORMANCE WITH ALL CONDITIONS STATED IN THE ABOVE CAPTIONED PERMIT...

DRILLERS LIC. NO.: M MD 553
DRILLERS SIGNATURE: [Signature]
LIC. NO.: D 942

SITE SUPERVISOR (sign. of driller or journeyman responsible for sitework if different from permittee)

DEPTH (nearest ft.)

Table for DEPTH with columns: 1, 2, 3, 4, 5, 6, 7, 8, 9, 11, 15, 17, 21, 23, 24, 26, 30, 32, 36, 38, 39, 41, 45, 47, 51. Includes SLOT SIZE and DIAMETER OF SCREEN.

GRAVEL PACK IF WELL DRILLED WAS FLOWING WELL INSERT F IN BOX 68

MDE USE ONLY (NOT TO BE FILLED IN BY DRILLER)
TELESCOPE CASING, LOG INDICATOR, OTHER DATA

C 3

PUMPING TEST

HOURS PUMPED (nearest hour): 8
PUMPING RATE (gal. per min.): 11
METHOD USED TO MEASURE PUMPING RATE: [Blank]
WATER LEVEL (distance from land surface):
BEFORE PUMPING: 17 ft.
WHEN PUMPING: 22 ft.
TYPE OF PUMP USED (for test): J (jet), S (submersible)

PUMP INSTALLED

DRILLER INSTALLED PUMP (CIRCLE) (YES or NO)
IF DRILLER INSTALLS PUMP, THIS SECTION MUST BE COMPLETED FOR ALL WELLS.
TYPE OF PUMP INSTALLED: J (jet)
CAPACITY: GALLONS PER MINUTE (to nearest gallon): 31
PUMP HORSE POWER: 37
PUMP COLUMN LENGTH (nearest ft.): 41
CASING HEIGHT (circle appropriate box and enter casing height): + above, - below

LATITUDE 3
LONGITUDE 7
(DEFAULT COORD. WGS 84)
NOTES: [Handwritten notes and diagram]