

W.P.I. - 9/19/84
AM - Around noon

Approved 9/16/84
Stinger
P 34201
A 30242

PERMIT

SEWAGE DISPOSAL SYSTEM

MARYLAND STATE DEPARTMENT OF HEALTH

HOWARD COUNTY
BUREAU OF ENVIRONMENTAL HEALTH
992-2330

ELLICOTT CITY

DISTRICT 4th.

DATE 8/9/84

INDEX

04-343018

Arthur Bell IS PERMITTED TO INSTALL ALTER

ADDRESS 10331 South Dolfield Road, Owings Mills, MD PHONE 363-0880

SUBDIVISION Roxbury Estates ROAD 4050 Roxmill Court LOT 16

PROPERTY OWNER John and Ann Klingler
ADDRESS 4517 Bennion Road
Wheaton, Maryland 20906

BUILDING PERMIT SIGNED
AND RETURNED

9/11/85 800 155 998-16 POOL

IF GARBAGE GRINDER IS USED INCREASE SEPTIC TANK CAPACITY BY 50% AND ABSORPTION AREA BY 22%.

GARBAGE GRINDER? YES NO

SEPTIC TANK CAPACITY 1000 1500 GALLONS

NUMBER OF BEDROOMS 1 5 BED ROOM
870 SQFT REQUIRED

TRENCHES - 174 sq. ft. per bedroom. Trench to be 2 feet wide. Inlet 5 feet below original grade. Bottom maximum depth 9 feet below original grade. Effective area begins at 5 feet below original grade with 4 feet of stone below distribution pipe. LOCATION: Start first trench 135 feet from the left lot line and 390 feet from the front lot line as seen when facing the property from Roxmill/343018 Court. Run trench(s) along level ground toward left lot line. NOTE: No trench to exceed 100 feet in length. If more than one trench used, a distribution box is required. Trenches to be installed on level ground. Call for inspection of trench(s) before and after gravel is installed. Provide 6" - 8" diameter cleanout and cap to grade or above on septic tank. If a Garbage disposal is used, increase septic tank capacity by 50% and increase absorbant sidewall area by 22%.

OR TO HAVE 2 TRENCHES 109 FT LONG INSTEAD OF THREE TRENCHES 9/15/84 RH

PLANS APPROVED BY Craig Williams DATE 8/19/83

COVER NO WORK UNTIL INSPECTED AND APPROVED.

NEITHER THE HOWARD COUNTY COUNCIL NOR THE HEALTH DEPARTMENT IS RESPONSIBLE FOR THE SUCCESSFUL OPERATION OF ANY SYSTEM.

NOTE: IF TRENCH IS USED CALL FOR INSPECTION BEFORE AND AFTER PLACING GRAVEL IN TRENCH.

NOTE: NO DRY WELL SHALL EXCEED 15 FOOT IN DIAMETER. NO ABSORPTION TRENCH TO EXCEED 100 FEET IN LENGTH.

NOTE: ALL PIPE FROM HOUSE TO SEPTIC TANK MUST BE CAST IRON OR SCHEDULE 40 PVC OR ABS.

PERMIT VOID AFTER THREE YEARS.

BUDG. PERMIT SIGNED
AND RETURNED 11/25/85

NOTE: INSTALL STAND PIPE ON SEPTIC TANK AND DRY WELL. STAND PIPES MUST BE 6 INCHES IN DIAMETER. CAST IRON, CONCRETE OR TERRA COTTA, OR PVC OR ABS ACCEPTED. IF TOP OF SEPTIC TANK IS DEEPER THAN 3 FEET MANHOLE TO GRADE REQUIRED.

Serial # 22659
Mwend post

*INSTALLER IS RESPONSIBLE FOR OBTAINING FINAL APPROVAL ON THIS PERMIT

*CALL 992-2330 FOR INSPECTION OF SEPTIC SYSTEMS.

EH - 2-1082

A 30242